
JINI XTRA







www.austroflamm.com

JINI XTRA



Dimensions and weight	
Height [mm]	1000
Width [mm]	486
Depth [mm]	406
Combustion chamber width [mm]	282
Combustion chamber height [mm]	400
Combustion chamber depth [mm]	254
Baking compartment width [mm]	-
Baking compartment height [mm]	-
Baking compartment depth [mm]	-
Warming drawer, width [mm]	-
Warming compartment height [mm]	-
Warming drawer, depth [mm]	-
Dimensions, a (with Austroflamm elbow piece) [mm]	1518
Dimensions, b (with Austroflamm elbow piece) [mm]	850
Dimensions, c (with Austroflamm elbow piece) [mm]	586
Dimensions, d (with Austroflamm elbow piece) [mm]	202
Flue pipe outlet, diameter [mm]	130
Outside air connection diameter [Ø mm]	125
Weight, basic appliance [kg]	100
Weight Xtra [kg]	101
Weight, HMS [kg]	-
Total weight inc. steel case (STM) [kg]	216
Total weight inc. ceramic case (KGM) [kg]	-
Total weight inc. soapstone case (SPM) [kg]	-
a: Safety distance to combustible materials, front [mm]	1000
b: Safety distance to combustible materials, left [mm]	270
c: Safety distance to combustible materials, rear [mm]	160
d: Safety distance to combustible materials, right [mm]	270
Safety distance to combustible materials, floor [mm]	0
Output	
Nominal heat efficiency [kW]	4.0
Minimum heat output [kW]	2.5

Maximum heat output [kW]	6.0	
Minimum room heating capacity [m³]	34	
Maximum room heating capacity [m³]	88	
Energy efficiency class	A+	
Data for the chimney sweep		ſ
Exhaust gas mass flow [g/s]	3.9	
Flue gas temperature [°C]	343	
Flue gas temperature [°C] Minimum delivery pressure at nominal heat output [Pa]	343 12	

Equipment	
Xtra heat storage technology	Standard
Heat Memory System	-
External air connection / operation independent of ambient air	Yes
Ash removal	Ash pan